

# DFO48G06PUIXDGL

## Ethernet 1000Mbps/POE

### Unmanaged Fiber Optic Switch

#### Multi-Drop



#### DESCRIPTION

The DFO48G06PUIXDGL Series are compact, field installable unmanaged, Ethernet Fiber POE Switches with 4 x 1000TX POE copper ports and 2 x 1000Base-X fiber ports for multi-drop topology transmission. Units are designed for today's edge appliance networks, feature high grade components, rugged temperature ratings – IP44 housings (no fan required) resists dust, dirt, moisture, insects and smoke. With 48VDC input, DIN rail mount, compliance with IEE802.3at - 30W per POE port, the DFO48G06PUIXDGL Series are a perfect solution for commercial and industrial IP Video surveillance installations.



#### FEATURES

- \* Unmanaged Ethernet 1000Mbps Fiber POE Switch for Multi-drop configuration
- \* 4x1000Base-TX Copper, 2x1000Base-X
- \* Auto-negotiation and auto-cross MDI-MDIX
- \* Full duplex flow/half-duplex Interface control
- \* Compliance IEE802.at 30W per Port 48V
- \* Ethernet 802.3af, 802.3at, 802.3u, 802.3x 100BASE-TX, 1000BASE-TX, 1000BASE-X
- \* Supports Reverse Connection
- \* Transmission mode: storage and forward
- \* System bandwidth > 40Gbps (non-jam)
- \* Power-on, Status and Data Traffic LEDs
- \* 20Km and 40Km SM Fiber Versions LC
- \* Standard DIN Rail Configurations
- \* 48VDC-52VDC (use 48VDC) input voltages
- \* Compliance with CE, FCC, ROHS, IP44

#### APPLICATIONS

- \* Homeland Security
- \* Correctional Centers
- \* Petrochemical Industry
- \* Corporate and Banking
- \* Casinos and Hospitality
- \* Health Care Centers
- \* Schools and Universities
- \* Government and Military
- \* Power Generating Plants
- \* Traffic Surveillance (ITS)

#### ORDERING INFORMATION

DFO48G06PUIXE9ADGL Unmanaged Ethernet POE Switch, 4 x 10/100Base-TX Copper, 2x1000BaseX Fiber Optic Ports TRX 20Km SM, Din Rail, 48VDC LC

DFO48G06PUIXF9ADGL Unmanaged Ethernet POE Switch, 4 x 10/100Base-TX Copper, 2x1000BaseX Fiber Optic Ports TRX 40Km SM, Din Rail, 48VDC LC




# DFO48G06PUiXDGL

## Ethernet 1000Mbps/POE

### Unmanaged Fiber Optic Switch

### Multi-Drop



#### Data Performance

Fiber ports: 2 x 1000Base-X LC  
 Electrical Ports: 4 x RJ-45 1000Base-TX POE  
 RJ-45 Ports Data Rate: 1000 Mbps, FDX and HDX modes  
 Auto-negotiation and auto-cross MDI-MDIX on RJ-45 ports  
 Network Standards: Ethernet IEEE 802.3at, 802.3u; IEEE 802.1af, 100BASE-TX, 1000BASE-T, 1000BASE-X

#### Mechanical Parameters

Enclosure: Robust sheet metal Aluminum  
 Dimensions H x W x D: 6.2"(158mm), 2.4"(60mm) 4.53"(115mm)  
 Weight: 1.8lbs (800g)  
 Cooling Method: Convection, case as heat sink  
 Mounting: DIN Rail

#### Power Supplies

Power Input: 48-52VDC voltages  
 Power Connector: Built-in screw terminal/jack  
 Power Consumption: <5 Watts

#### Environmental Parameters

Operating Temperature: -40°C to 85°C  
 Operating Humidity: 5% - 95% (non-condensing)

#### LED Indicators

Power: ON for power applied  
 10/100 per RJ-45 port: Steady ON for 100 Mb, OFF for 10 Mb speed  
 LK/ACT per port: Steady ON for LINK with no traffic, blinking for Activity  
 F/H per port in end: Steady ON for F/D mode, OFF for H/D mode

#### Regulatory Compliance

Agencies: CE, FCC, ROHS, IP44  
 EMC disturbance: EN55022  
 EMC immunity: EN50082-2  
 EN55022: Class A  
 Electrostatic/ EMI: IEC61000-4-2; 61000-4-3  
 Transient Response/ Surge: IEC61000-4-4; 61000-4-5  
 Radio Frequency: IEC61000-4-6  
 Vibration/Shock: IEC60068-2-6; 60068-2-27  
 Manufactured to: ISO9001:2000 Standards

#### Optical performance

	Singlemode	Multimode
Fiber type	Singlemode	Multimode
Wavelength	Laser 1310nm	Laser 850nm (500m)
Output Power	-26 dBm/-15 dBm	-18dBm
Receiver Sensitivity	-38 dBm	-35dBm
Optical Loss Budget	12 dB/23 dB	17dB



[www.dantesecurity.net](http://www.dantesecurity.net)

Lynbrook, NY USA

[sales@dantesecurity.net](mailto:sales@dantesecurity.net)